

未注公差/General tolerances(mm)														 0.1/10 
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	

5	Grounding	Copper alloy	Sn plated
4	Current carrier	Copper	Sn plated
3	Spring	Stainless steel	/
2	Button	PA66-GF	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	/	/	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	Ⅲ/3	Ⅲ/2	Ⅱ/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	/	/
额定脉冲电压(KV)/Rate Impulse	8	/	/
螺丝扭矩/Torque Tightening(N·m/Lb.in)	/		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm ²)	24~10 / 0.2~4.6(SOL)		
间距/Pitch(mm)/线数范围/Poles	6.2		
剥线长度/Stripping length(mm)	11~13		

 DEGSON			MATERIAL:		SURFACE/COLOR:			
APPD: 李根芳			2024.07.03		MAT NO./REV: 11040000047-2 / 00		MAT STATUS: work	
CHKD: 马恩开			2024.07.03		DS4-PE-01P-1C-00L(H)			
DRFT: 宗明忠			2024.06.24					
  A4		 (inch)		DRAWING NO. 200272091	TYPE CUSTOMER DRAWING	DRAWING STATUS 已发布	SCALE 2:1	SHEET 1/1

01		EAC lettering removal	宋明忠	2024.06.2
REV	ECN	DESCRIPTION	DRFT	DATE