

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless authorized in writing. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、商标、商号、名称、域名、其他知识产权等权利外，其他权利均归本公司所有。未经许可，不得复制或传播。

FOR-1755 Rev.1.8

2

3

4

5

6

34.7

29.3

77

未注公差/General tolerances (mm)

0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
3	6	10	18	30	50	80	120	180	250	315	400	500	>500	±2'
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	

A

B

6.2

35.3

34.4

①

②

③

④

5



MATERIAL:	SURFACE/COLOR:
MAT NO./REV: 11040001524-1 / 00	MAT STATUS: work

APPD: 李根芳	2024.01.31
CHKD: 马恩升	2024.01.31
DRFT: 姜海文	2024.01.31

NAME	DS4-QU-PE-01P-1C-00L (H)
------	--------------------------

DRAWING NO. 200269466	TYPE CUSTOMER DRAWING	DRAWING STATUS 已发布	SCALE 2:1	SHEET 1/1
-----------------------	-----------------------	--------------------	-----------	-----------

00	/	NEW DRAWING	姜海文	2024.01.31
REV	ECN	DESCRIPTION	DRFT	DATE

5	Grounding	Copper alloy	Sn plated
4	Current carrier	Copper	Sn plated
3	Spring	Stainless steel	/
2	Button	PA66-GF	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:		B	C
额定电压/电流/Rated Voltage (V)/Current (A)		/	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2
额定电压/电流/Rated Voltage (V)/Current (A)		/	/
额定脉冲电压 (KV)/Rate Impulse		8	/
螺栓扭矩/Torque Tightening (N · m/Lb.in)		/	
线径范围 (硬线和软线)/Wire Range (rigid and flexible) (AWG/mm ²)		24~10 / 0.2~4.6 (SOL)	
间距/Pitch (mm)/线数范围/Poles		6.2	
剥线长度/Stripping length (mm)		10~12	
使用温度范围/Operating temperature (°C)		-40~+105	
符合RoHS环保要求/Conform to RoHS		Yes	
标准颜色编号/Standard color number:		/	

C

D

1

2

3

4

5

6