

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、商标、名称权、商号权、域名权、其他知识产权等权利外，本公司保留所有权利。

FOR-1755 Rev.1.6

2

3





4

5

6

未注公差/General tolerances (mm)

0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
3	6	10	18	30	50	80	120	180	250	315	400	500		±2°
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	



5	Current carrier 2	Copper	Sn Plated
4	Current carrier 1	Copper	Sn Plated
3	Spring	Stainless steel	/
2	Button	PA66+GF%	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:		B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)		300/20	300/20	300/10
IEC 标准/IEC Standard:				
过压类别/Overtoltage Category/污染等级/Pollution Degree		III/3	III/2	II/2
额定电压/电压/Rated Voltage(V)/Current(A)		500/22	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		6	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)		26- 12/ 0.2- 2.5,4(Sol)		
间距/Pitch(mm)/线数范围/Poles		5.20/NE- 01P		
剥线长度/Stripping length(mm)		11~ 12		
使用温度范围/Operating temperature(°C)		-40~ + 105		
符合 RoHS 环保要求/Conform to RoHS		Yes		

MATERIAL:		SURFACE/COLOR:	
MAT NO./REV: 11040001496-1 / 00		MAT STATUS: work	
APPD: 李根芳	2024.07.04	NAME	
CHKD: 马恩升	2024.07.03	DSKK2.5-01P-11-00L (H)	
DRFT: 李根芳	2024.07.03	DRAWING NO.	TYPE
		200073134	CUSTOMER DRAWING
		DRAWING STATUS	SCALE
		已发布	1:1
		SHEET	1/1

03	ECN	Explosion-proof lettering added	李根芳	2024.07.03
REV	ECN	DESCRIPTION	DRFT	DATE

1

2

3

4

5

6